



238 CRANBERRY DR
STUARTS DRAFT, VA. 24477

INSTRUCTIONS:

EARLY MODEL CORVAIR/ CORVETTE HEADLIGHT/ WIPER/ IGNITION BEZEL TOOL

THE "PIN" END OF THIS TOOL MAY BE USED TO ENGAGE AND REMOVE THE HEADLIGHT SWITCH RETAINING NUT AFTER THE "PULL" KNOB HAS BEEN REMOVED. IT CAN BE REMOVED BY PULLING THE KNOB OUT ALL THE WAY TURNING ON HEADLIGHTS (DON'T FOGET TO DISCONNECT BATTERY) AND THEN DEPRESS THE SPRING-LOADED BUTTON LOCATED ON THE SIDE OF THE SWITCH UNDER THE DASH AND CONTINUE PULLING KNOB TO REMOVE. THEN INSERT THE PIN END OF THE TOOL INTO THE SWITCH HOLE AND TURN COUNTERCLOCKWISE TO REMOVE THE SMALL SLOTTED NUT.

REMOVE THE SMALL SCREW LOCATED ON THE SIDE OF THE WIPER SWITCH KNOB AND USE THE END OF THE TOOL WITH A HOLE IN IT TO REMOVE THE SLOTTED NUT.

THANKS, AND HAPPY MOTORING!

RUSSELL DAVIS

(757) 642-0665

bluechipmach.rd@gmail.com

PLEASE VISIT www.bluechiptools.com to view all my tools and items.



IGNITION BEZEL ADAPTER

****THE SET SCREWS IN THE ADAPTER ARE MEANT TO BE TIGHT!!****

A SPECIAL L- 3 FIT TAP WAS USED TO PRODUCE THE SET SCREW THREADS ON THE ADAPTER.

THEY NEED TO BE TIGHT ENOUGH SO THEY WON'T MOVE WHEN THE BEZEL IS BEING REMOVED. SOME ARE VERY TIGHT; HOWEVER, I CAN NOT CONTROL THE PITCH DIAMETER OF THE SET SCREWS.

THEY ARE PURCHASED FROM McMASTER CARR. THEY HAVE BEEN PURCHASING THE SET SCREWS FROM THE SAME MANUFACTURER FOR THE LAST TWENTY YEARS, BUT THEY STILL HAVE A TOLERANCE THAT AFFECTS THE FIT. IF USED REPEATLY, THE FIT WILL LOOSEN AND YOU MAY WANT TO USE SOME BLUE LOCTITE TO KEEP THEM FROM MOVING AROUND. REMEMBER; THE IGNITION BEZELS DON'T HAVE MUCH AREA TO "GRAB" ON TO.

GENERALLY, IF THE SET SCREW IS FLUSH WITH THE OUTSIDE OF THE TOOL, THEY WILL ENGAGE THE BEZEL WELL.

KEEP THE TOOL PUSHED SOLIDLY AGAINST THE BEZEL WHEN REMOVING OR INSTALLING TO ACHIEVE PROPER ENGAGEMENT.

IF YOU HAVE ANY ISSUES THAT I NEED TO BE AWARE OF, PLEASE E-MAIL ME.

THANKS, AND HAPPY MOTORING! - RUSSELL DAVIS

(757) 642-0665

bluechipmach.rd@gmail.com

PLEASE VISIT www.bluechiptools.com to view all my tools and items.